

# RAD PNEUMATIC 10GX

Imperial Part No. 12818

## SPECIFICATIONS

**Torque Range Ft. lbs.:** 200 - 1,000 Ft. lbs.

**Torque Range Nm:** 271 - 1,356 Nm

**Speed:** 20 RPM

**Weight:** 3.6 Kg (Excluding reaction arm and impact socket)

**Square Drive:** 3/4"

**Noise Level:** 80 dB

**Accuracy:** +/- 4%

**Repeatability:** +/-2%

**Motor Type:** Planetary gearbox, pneumatic powered

**Metric Equivalent:** RAD 14GX-M Part No. 19149



Site Box\*  
PN: CPB555545

*\*Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on*

## INCLUDED

- RAD Pneumatic 10GX tool
- Reaction Arm (PN: 19260)
- Retaining Ring (PN: 12733)
- 3 Meter Hose
- Tool Holder
- FRL unit
- Instruction Manual
- Safety Guide
- Calibration Certificate
- Weatherproof storage case (Australia only, see disclaimer)\*

## DIMENSIONS



## SAFETY

### HAND GUARD



PN: 21436

### OPERATOR SAFETY VALVE (OSV)



PN: OSV-120

### LIFTING RING



PN: 15960

### TOOL HANDLE



PN: 15962

### TOOL HANDLE ONE EYE



PN: 19827

### TOOL HANDLE TWO EYES



PN: 30912

## REACTION ARMS

### CAST ARM



PN: 19260  
(included in kit)

### ANGLED



PN: 17235

### DEEP ANGLED SOCKET



PN: 17236

### 90 DEGREE



PN: 13366

### 90 DEGREE DEEP SOCKET




PN: 13367

### DOUBLE ENDED



PN: 13368

### STANDARD SLIDING ARM 60 - 180 mm



PN: CRP12818-1

### RETAINING RING



PN: 12733  
(included in kit)

V3