

RAD PNEUMATIC 110DX

Imperial Part No. 26152

SPECIFICATIONS

Torque Range Ft. lbs.: 4,000 - 11,000 Ft. lbs.
Torque Range Nm: 5,500 - 15,000 Nm
Speed: 3 RPM
Weight: 18.9 Kg (Excluding reaction arm and impact socket)
Square Drive: 1^{1/2} "
Noise Level: 85 dB
Accuracy: +/- 4%
Repeatability: +/- 2%
Motor Type: Planetary gearbox, pneumatic powered
Metric Equivalent: 150DX Part No. 26153



**Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on*

DIMENSIONS



INCLUDED

- RAD Pneumatic 110DX tool
- Angled Reaction Arm (PN: 23776)
- Retaining Ring (PN: 18301)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator (FRL) unit
- Instruction Manual and Safety Guide
- Calibration certificate
- Weatherproof storage case / Site Box (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: CTG-60-85	OPERATOR SAFETY VALVE (OSV)  PN: OSV-200	LIFTING RING  PN: TBA
TOOL HANDLE  PN: TBA (included in kit)	TOOL HANDLE ONE EYE  PN: 26634	TOOL HANDLE TWO EYES  PN: TBA

CAST ARM  PN: 25664	ANGLED  PN: 23776 (included in kit)	ANGLED DEEP SOCKET  PN: 26157
90 DEGREE  PN: ETO	90 DEGREE DEEP SOCKET  PN: ETO	DOUBLE ENDED  PN: 26158
STANDARD SLIDING ARM  PN: ETO	RETAINING RING  PN: 18301 (included in kit)	V3