

RAD PNEUMATIC 25GX

Imperial Part No. 12377

SPECIFICATIONS

Torque Range Ft. lbs.: 500 - 2,500 Ft. lbs.

Torque Range Nm: 700 - 3,400 Nm

Speed: 9 RPM

Weight: 6.1 Kg (Excluding reaction arm and impact socket)

Square Drive: 1 "

Noise Level: 85 dB

Accuracy: +/- 4%

Repeatability: +/-2%

Motor Type: Planetary gearbox, pneumatic powered

Metric Equivalent: 34GX Part No. 13565



Site Box*

PN: CPB555545

*Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on

DIMENSIONS



REACTION ARMS


INCLUDED

- RAD Pneumatic 25GX tool
- Arm (PN: 18250)
- Retaining Ring (PN: 10509)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator unit
- Instruction Manual and Safety Guide
- Calibration Certificate
- Weatherproof storage case (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: 21437	OPERATOR SAFETY VALVE (OSV)  PN: OSV-180	LIFTING RING  PN: 14845
TOOL HANDLE  PN: 15959	TOOL HANDLE ONE EYE  PN: 19823	TOOL HANDLE TWO EYES  PN: 19954

CAST ARM  PN: 23526	ANGLED  PN: 18863	DEEP ANGLED SOCKET  PN: 18864
90 DEGREE  PN: 18250 (included in kit)	90 DEGREE DEEP SOCKET  PN: 18251	DOUBLE ENDED  PN: 10516
STANDARD SLIDING ARM  PN: CRP12377-17	RETAINING RING  PN: 10509	V3