

RAD PNEUMATIC 30DX

Imperial Part No. 22238

SPECIFICATIONS

Torque Range Ft. lbs.: 900 - 3,000 Ft. lbs.

Torque Range Nm: 1,200 - 4,000 Nm

Speed: 8 RPM

Weight: 6.7 Kg (Excluding reaction arm and impact socket)

Square Drive: 1"

Noise Level: 85 dB

Accuracy: +/- 4%

Repeatability: +/-2%

Motor Type: Planetary gearbox, pneumatic powered

Metric Equivalent: 40DX Part No. 24717



Site Box*
PN: CPB555545

*Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on

DIMENSIONS



INCLUDED


- RAD Pneumatic 30DX tool
- Angled Arm (PN: 21482)
- Retaining Ring (PN: 21474)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator (FRL) unit
- Instruction Manual and Safety Guide
- Calibration certificate
- Weatherproof storage case (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: 21437	OPERATOR SAFETY VALVE (OSV)  PN: OSV-180	LIFTING RING  PN: 26800
TOOL HANDLE  PN: 26758	TOOL HANDLE ONE EYE  PN: 26751	TOOL HANDLE TWO EYES  PN: TBA

REACTION ARMS

CAST ARM  PN: 24639	ANGLED  PN: 21482 (included in kit)	DEEP ANGLED SOCKET  PN: 24814
90 DEGREE  PN: 25981	90 DEGREE DEEP SOCKET  PN: 27231	DOUBLE ENDED  PN: 25437
STANDARD SLIDING ARM 80 - 250mm  PN: CRP22238-1-TB	RETAINING RING  PN: 21474	V3