

RAD PNEUMATIC 50DX

Imperial Part No. 20248

SPECIFICATIONS

Torque Range Ft. lbs.: 1,500 - 5,000 Ft. lbs.
Torque Range Nm: 2,000 - 7,000 Nm
Speed: 6.7 RPM
Weight: 10.6 Kg (Excluding reaction arm and impact socket)
Square Drive: 1 1/2"
Noise Level: 85 dB
Accuracy: +/- 4%
Repeatability: +/- 2%
Motor Type: Planetary gearbox, pneumatic powered
Metric Equivalent: 70DX Part No. 26133



Site Box*
PN: CPB555545

*Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on

DIMENSIONS



REACTION ARMS

INCLUDED

- RAD Pneumatic 50DX tool
- Angled Arm (PN: 25286)
- Retaining Ring (PN: 21455)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator (FRL) unit
- Instruction Manual and Safety Guide
- Calibration certificate
- Weatherproof storage case (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: 21600	OPERATOR SAFETY VALVE (OSV)  PN: OSV-200	LIFTING RING  PN: TBA
TOOL HANDLE  PN: TBA	TOOL HANDLE ONE EYE  PN: 26674	TOOL HANDLE TWO EYES  PN: TBA

CAST ARM  PN: 25665	ANGLED  PN: 25286 (included in kit)	ANGLED DEEP SOCKET  PN: 26118
90 DEGREE  PN: 29422	90 DEGREE DEEP SOCKET  PN: 29425	DOUBLE ENDED  PN: 26119
STANDARD SLIDING ARM 80 - 250mm  PN: ETO	RETAINING RING  PN: 21455 (included in kit)	V3