

RAD PNEUMATIC 60DX

Imperial Part No. 15328

SPECIFICATIONS

Torque Range Ft. lbs.: 2,000 - 6,000 Ft. lbs.

Torque Range Nm: 2,700 - 8,000 Nm

Speed: 6.6 RPM

Weight: 12.4 Kg (Excluding reaction arm and impact socket)

Square Drive: 1 1/2"

Noise Level: 85 dB

Accuracy: +/- 4%

Repeatability: +/-2%

Motor Type: Planetary gearbox, pneumatic powered

Metric Equivalent: 80DX Part No. 15805



Site Box*
PN: CPB555545

Shown with tool holder which comes standard with a Pneumatic 60DX Tool Kit

**Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on*

DIMENSIONS



REACTION ARMS

INCLUDED

- RAD Pneumatic 60DX tool
- Angled Arm (PN: 15375)
- Retaining Ring (PN: 15367)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator (FRL) unit
- Instruction Manual and Safety Guide
- Calibration certificate
- Weatherproof storage case (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: 21605	OPERATOR SAFETY VALVE (OSV)  PN: OSV-200	LIFTING RING  PN: 12729
TOOL HANDLE  PN: 15956 (included in kit)	TOOL HANDLE ONE EYE  PN: 19819	TOOL HANDLE TWO EYES  PN: 22384

CAST ARM  PN: 23530	ANGLED  PN: 15375 (included in kit)	ANGLED DEEP SOCKET  PN: 15788
90 DEGREE  PN: 16368	90 DEGREE DEEP SOCKET  PN: 17643	DOUBLE ENDED  PN: 15790
STANDARD SLIDING ARM 80 - 250mm  PN: ETO	RETAINING RING  PN: 15367 (included in kit)	V3