

RAD PNEUMATIC 80DX

Imperial Part No. 18558

SPECIFICATIONS

Torque Range Ft. lbs.: 2,500 - 8,000 Ft. lbs.
Torque Range Nm: 3,400 -11,000 Nm
Speed: 4 RPM
Weight: 13.7 Kg (Excluding reaction arm and impact socket)
Square Drive: 1^{1/2} "
Noise Level: 85 dB
Accuracy: +/- 4%
Repeatability: +/-2%
Motor Type: Planetary gearbox, pneumatic powered
Metric Equivalent: 110DX Part No. 23229



Site Box*
PN: CPB555545

**Disclaimer: Site Box not included in tool kits for shipments outside Australia; available as an optional add-on*

DIMENSIONS



INCLUDED

- RAD Pneumatic 80DX tool
- Cast Reaction Arm (PN: 23144)
- Retaining Ring (PN: 11930)
- 3 Meter Hose
- Tool Holder
- Filter/Regulator/Lubricator (FRL) unit
- Instruction Manual and Safety Guide
- Calibration certificate
- Weatherproof storage case (Australia only, see disclaimer)*

SAFETY

ETO = Engineered to order / TBA = To Be Advised

HAND GUARD  PN: CTG-60-85	OPERATOR SAFETY VALVE (OSV)  PN: OSV-200	LIFTING RING  PN: 15504
TOOL HANDLE  PN: 16221 (included in kit)	TOOL HANDLE ONE EYE  PN: 22931	TOOL HANDLE TWO EYES  PN: 25195

REACTION ARMS

CAST ARM  PN: 23144 (included in kit)	ANGLED  PN: 17239	ANGLED DEEP SOCKET  PN: 13508
90 DEGREE  PN: 12885	90 DEGREE DEEP SOCKET  PN: 13508	DOUBLE ENDED  PN: 13509
STANDARD SLIDING ARM  PN: ETO	RETAINING RING  PN: 11930 (included in kit)	