

B-RAD[®] XTREME 3000-C 4000-M-C

PN: 34435

PN: 34436



Screen Display



RAD Torque is bringing shaft retention to the B-RAD X Series. B-RAD X 3000-C/4000-M-C is a cordless shaft retention tool engineered for hard-to-reach fastening applications that have long been the domain of bulky pneumatic equipment.

SPECIFICATIONS Imperial (Metric)

Torque Ranges:

250 ft-lb – 3000 ft-lb (400 Nm - 4000 Nm)

Speed: **3.9 RPM**

Weight: **17 lbs. (7.9 Kg)**


Square Drive: **1"**

Noise Level: **75 dBs**

Repeatability: **+/-2%**

Accuracy: **4% Accuracy to Target**

DIMENSIONS



Dimension A
in (mm)

11.75 (298)

Dimension B
in (mm)

3.25 (83)

Dimension C
in (mm)

3.62 (92)

Dimension D
in (mm)

13.75 (349)

TOOLKIT

- Cast Reaction Arm (25665)
- (2) 18V batteries
- Charger
- Durable case



Class 1 Division 2
Group A, B, C, D T4



*Shaft not Included




Custom shafts available on request based on application

SUITABLE REACTION ARMS

Angled
PN: 21482



Double Ended Arm
PN: 25437



Double Ended Blank
PN: 25437



Blank
PN: 24813



Deep Socket
PN: 24814



Retaining Ring
PN: 21474



radtorque.com