

B-RAD[®] SELECT EGX-R 1000-2 1400-M-2

PN: 32449

PN: 32449



ScreenDisplay



The B-RAD Select EGX-R 1000-2/1400-M-2 is engineered for railway bolting applications. Based on the proven Select platform, it incorporates an extension tube from the adapter plate to the gearbox, improving ergonomics by minimizing operator bending during use.

SPECIFICATIONS Imperial (Metric)

Torque Ranges:

200 ft-lb – 1000 ft-lb (300 Nm – 1400 Nm)

Speed: **71 RPM**

Weight: **12.3 lbs. (5.6 Kg)**


Square Drive: **.75"**

Noise Level: **90 dBs**

Repeatability: **+/-2%**

Accuracy: **+/-5%**

DIMENSIONS



Dimension A in (mm)	Dimension B in (mm)
------------------------	------------------------

33.42 (848.86)	2.47 (62.86)
----------------	--------------

Dimension C in (mm)	Dimension D in (mm)
------------------------	------------------------

2.62 (66.67)	10.3 (262.62)
--------------	---------------

TOOLKIT

- Double Ended Arm (13368)
- (2) 18V batteries
- Charger
- Durable case



ACCESSORIES

**Double Safety
Trigger Option**
PN: 25949




Class 1 Division 2
Group A, B, C, D T4

SUITABLE REACTION ARMS


Cast Arm
PN: 19260




Double Ended Arm
PN: 13368



Double Ended Blank
PN: 34756



Blank
PN: 34735



Deep 90 Degree
PN: 13367



Retaining Ring
PN: 12733

