

B-RAD[®] XTREME 1000 1400-M

PN: 32651

PN: 32652



Level up your torque power with the all-new B-RAD X 1000/1400-M. Engineered for superior performance in a compact, high-efficiency design, it delivers the precision and control needed for demanding industrial applications while bringing the award-winning B-RAD X Series technology to a lower torque range.

SPECIFICATIONS Imperial (Metric)

Torque Ranges:

100 ft-lb – 1000 ft-lb (140 Nm - 1400 Nm)

Speed: **14.5 RPM**

Weight: **12.3 lbs. (5.6 Kg)**


Square Drive: **.75"**

Noise Level: **78 dBs**

Repeatability: **±2%**

Accuracy: **±3.5% accuracy full scale**

DIMENSIONS



Dimension A
in (mm)

10.63 (270)

Dimension B
in (mm)

2.48 (63)

Dimension C
in (mm)

3.62 (92)

Dimension D
in (mm)

13.87 (352)

TOOLKIT

- Cast Reaction Arm (19260)
- (2) 18V batteries
- Charger
- Durable case



Class 1 Division 2
Group A, B, C, D T4




SUITABLE REACTION ARMS

Angled
PN: 17235



Double Ended Arm
PN: 13368



Double Ended Blank
PN: 34756



Blank
PN: 34753



Deep Socket
PN: 13367



Retaining Ring
PN: 12733



radtorque.com